



A CSW Industrials Company

PRODUCT DATA SHEET

PYROSEAL™

Furnace and retort cement

Description

Pyroseal™ is a smooth, creamy, easy spreading furnace and retort cement that sticks where you put it. For high temperature sealing and bonding. Shrink-proof, crack-proof. Use in combustion chambers and for sealing doors and flue pipes.

Applications

Pyroseal is recommended for use on high temperature refractory surfaces found in fireboxes and other parts of furnaces, boilers, stoves and stokers used for comfort heating. It works as well on flue pipes, clean outs, ducts, and chimney collars. When cured, Pyroseal is, fire-proof, acid resistant, shrink-proof and crack-proof.

Instructions for Use

READ ALL DIRECTIONS, SDS AND WARNINGS ON LABEL BEFORE USING

SURFACE PREPARATIONS:

Clean joint thoroughly by scraping off old cement, wire brushing and rinsing with water. To remove oil and grease, use a fast evaporating solvent (such as ZIPPTM).

APPLICATION:

Using fingers, work a thin prime coat into pores of casting, then trowel smooth. Place casting or section in place, filling joints completely. DO NOT TWIST. Scrape excess off and smooth to feather edge. First firing should begin at low temperature. Slowly increase temperature to allow cement to harden (without pores) into a durable solid body. Do not start with a hot fire. After application, wash hands with soap and water. Keep container tightly closed or covered with a wet cloth during application.

For additional technical information, call Toll Free 1-800-231-3345



Characteristics | Features

- Contains no asbestos or OSHA restricted fibers
- Shrink-proof
- Crack-proof
- Low freezing point
- Fire-proof
- Acid resistant

Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Ft per Case
68616	6 Lbs.	8	52	1.204
68618	12 Lbs.	4	53	1.33

Specifications

Wt/Gal @ 77°F	11.9
Flash Point SETA CC	None
Color	Gray
Shelf Life	2 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances

Precautionary Statements

Refer to Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300

For additional Technical Information Call Toll Free 1-800-231-3345

Limited Warranty



For more information on our product limited warranty, visit RectorSeal.com

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2021 RectorSeal. All rights reserved. R50348-1121